

1. Company Identification and Product Hazard Overview:

Product Name : Cyclohexylamine

Synonyms : Aminocyclohexane; Hexahydroaniline

Recommended Use: Used as a corrosion inhibitor in boiler feed water and has important applications as a chemical

intermediate in insecticides, dry-cleaning soaps, gas absorbents, rubber chemicals, and plasticizers

Manufactured for : NORTH Metal and Chemical Company

P. O. Box 1985 York, PA USA 17405 Tel: 717-845-8646 P. O. Box 1985 York, PA USA 17403 Fax: 717-846-7350

Email: north@nmc-nic.com Website: www.nmc-nic.com

In Case of Emergency: Call CHEMTREC (24H): 1-800-424-9300

2. Hazard Identification:

GHS Classification:

Flammable Liquids (Category 3)

Acute Toxicity, Oral (Category 3)

Acute Toxicity, Dermal (Category 3)

Skin Corrosion (Category 1B)

Serious Eye Damage (Category 1)

Reproductive Toxicity (Category 2)

Acute Aquatic Toxicity (Category 3)

Signal Word: DANGER

Pictograms: Flammable, Acute Toxicity, Health Hazard, Corrosion









Hazard Statements:

H226 : Flammable liquid and vapor

H301 + H311 : Toxic if swallowed or in contact with skin

H314 : Causes severe skin burns and serious eye damage.

H318 : Causes serious eye damage

H361 : Suspected of damaging fertility or the unborn child

H402 : Harmful to aquatic life

2. Hazard Identification:

Precautionary Statements:

Prevention:

P201 : Obtain special instructions before use

P202 : Do not handle until all safety precautions have been read and understood

P210 : Keep away from heat/sparks/open flames/hot surfaces - No smoking

P233 : Keep container tightly closed

P241 : Use explosion-proof electrical/ventilating/lighting equipment

P242 : Use only non-sparking tools

P243 : Take precautionary measures against static discharge

P264 : Wash contact area thoroughly after handling

P270 : Do not eat, drink, or smoke when using this product

P273 : Avoid release to the environment

P280 : Wear protective gloves/protective clothing/eye protection/face protection.

P281 : Use personal protective equipment as required

P303 + P361 +P353 : IF ON SKIN or hair: Remove/Take off immediately all contaminated clothing. Rinse skin with

water/ shower

P305 + P351 +

P338 + P310 : IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician

P301 + P310 + P330 : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse Mouth

P301 + P330 + P331 : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P304 + P340 + P310 : IF INHALED: Remove person to fresh air and keep in position comfortable for breathing

P308 + P313 : IF exposed or concerned: Get medical advice/attention

P363 : Wash contaminated clothing before reuse.

P370 + P378 : In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P403 + P235 : Store in a well-ventilated place. Keep cool.

P273 + P405 : Avoid release to the environment. Store Locked Up.

P501 : Dispose of contents/container in accordance with local/state/federal regulations.

3. Composition/Information on Ingredient:

Chemical Name : Cyclohexylamine

| Substance: | CAS Number: | EC | Compo. (%) |
|-----------------|-------------|-----------|-------------|
| Cyclohexylamine | 108-91-8 | 203-629-0 | >99.7 % |



4. First Aid Measures:

General Advice: : Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous

area.

Eyes : Flush skin with running water for at least fifteen minutes. Remove any contact lenses. Get medical aid/

attention immediately. Continue to rinse eyes during transport to the hospital.

Skin: Remove contaminated clothing. Wash skin with plenty of running water and soap. Take victim

immediately to the hospital. Consult a physician.

Ingestion: If the product is swallowed, first rinse mouth. Give small amount of water to drink. Call doctor/

physician/poison center immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person. If a person vomits, place him/her in recovery position so the vomit does not enter

lungs.

Inhalation: If safe to do so, remove individual from further exposure. Keep warm and at rest. If breathing has

ceased, give artificial respiration. Do not give mouth to mouth resuscitation. Get medical attention/

consult a physician immediately.

Note to Physician : Treat symptomatically.

PPE for first responders: Gloves and safety goggles are highly recommended.

5. Fire Fighting Measures:

Flash Point (°C) : 28 °C (82.4 °F) - closed cup

Flammable Limits: Upper explosion limit: 9.4% (V); Lower explosion limit: 1.6% (V)

Auto ignition Temp. : Not available.

Flammable Class : Not available.

General Hazard: Evacuate personnel downwind in-order to avoid inhalation of irritating and/or harmful fumes and smoke.

Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

Special hazards arising

from the substance : Carbon oxides, Nitrogen Oxides (NOx)

Fire Fighting Procedures: Hazardous decomposition and combustion products such as carbon/nitrogen oxides can be formed if

product is burning. Cool exposed containers with water spray to prevent over heating.

Fire Fighting Equipment: Respiratory and eye protection are required for fire fighting personnel. Full protective equipment

(bunker gear) and self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. Evacuate area and fight fire from safe distance or a protected location. Move

fire-exposed containers, if allowable without sacrificing the safety of the firefighters. If possible,

firefighters should control run-off water to prevent environmental contamination.

6. Accidental Release Measures:

Protective Gear for

Personnel: Wear respiratory protection. Avoid breathing vapors, mist, or gas. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to

form explosive concentrations. Vapors can accumulate in low areas.

Environmental

Precaution : Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the

environment must be avoided.

Methods and materials for containment and

cleaning up : Contain spillage, and then collect with an electronically protected vacuum cleaner or by wet-brushing

and place in container for disposal according to local regulations.

Release Notes: If spill could potentially enter any waterway, including intermittent dry creeks, contact local authorities.



7. Handling and Storage:

Handling

: Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Keep away from sources of ignition. No smoking. Take measures to prevent the build up of electrostatic charge.

Storage

: Store in a cool, dry well-ventilated area. Keep containers closed and up right when not in use. Keep product isolated from incompatible materials/conditions. Handle under inert gas. Protect from moisture. Air sensitive. Storage class (TRGS 510): Flammable Liquids

8. Exposure Controls and Personal Protection:

Components with workplace control parameters

| Component | CAS-No. | Value | Control | Basis |
|-----------------|----------|--|---------------|-----------------------------------|
| | | | parameters | |
| Cyclohexylamine | 108-91-8 | TWA | 10.000000 ppm | USA. ACGIH Threshold Limit Values |
| | | | | (TLV) |
| | Remarks | Upper Respiratory Tract irritation | | |
| | | Eye irritation | | |
| | | Not classifiable as a human carcinogen | | |
| | | TWA | 10 ppm | USA. ACGIH Threshold Limit Values |
| | | | | (TLV) |
| | | Upper Respiratory Tract irritation | | |
| | | Eye irritation | | |
| | | Not classifiable as a human carcinogen | | |
| | | TWA | 10.000000 ppm | USA. NIOSH Recommended |
| | | | 40.000000 | Exposure Limits |
| | | | mg/m3 | |

Engineering Controls

: Use appropriate engineering controls to avoid contact with skin, eyes, and clothing. Wash hands before breaks and immediately after handling the product.

Personal Protective Equipment

Eyes and face: Tightly fitting safety goggles. Face shield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH.

Skin: Avoid direct contact with skin. Wear rubber gloves, apron, boots or whole bodysuit when handling this product. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of any contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection: Complete suit protecting against chemicals; flame retardant anti-static protective clothing. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at the specific work place.

Respiratory: Where risk assessment shows air-purifying respirators are appropriate, use full-face respirator with multi-purpose combination respirator cartridges as a back up to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH.

Work Hygienic Practices: Facilities storing or using this material should be equipped with emergency eyewash, and a safety shower. Good personal hygiene practices should always be followed.

Control of Environmental

Exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.



9. Chemical and Physical Properties:

 Appearance
 : Liquid
 Lower Explosive Limit
 : 1.6% (V)

 Odor
 : Characteristic (amine-like)
 Upper Explosive Limit
 : 9.4% (V)

Odor threshold : Not available Vapor Pressure : 31 hPa (23 mmHg) @ 37.7°C

Color : Light yellow Vapor Density

pH : 11.5 @ 100 g/l @ 20°C Relative Density : 0.867 g/cm³ @ 25°C

Melting Point : -17°C (1°F) - lit.

Solubility : Soluble in Water

Freezing Point : 3°F

Boiling Range : 134°C (273°F) - lit. Partition coefficient (n-octanol/water) : log POW: 1.4

Flash Point : 28°C (82.4°F) - closed

Viscosity (cSt) @ 25 °C cup: Not available Auto Ignition Temp. : 293.3°C

Evaporation Rate : Not available

10. Stability and Reactivity:

Stability : The product is stable under recommended storage conditions.

Possibility of

Hazardous Reactions: Vapors may form explosive mixture in the air

Hazardous

Decomposition Products: No data available

Incompatible Materials: Strong oxidizing agents, Carbon Dioxide, sodium hypochlorite, Organic acids, Mineral acids, Peroxides

Conditions to Avoid : Heat, flames, sparks

11. Toxicological Information:

Acute Toxicity Data:

LD50 Oral - Rat - 300 mg/kg LC50 Inhalation - Rat - 7,500 mg/m³

Remarks: Behavioral - Excitement; muscle contraction or spasticity

LD50 Dermal - Rabbit - 277 mg/kg

Skin corrosion/irritation:

Skin - Rabbit

Result: Severe skin irritation - 24h

Serious eye damage/eye irritation:

Eyes - Rabbit

Result: Severe eye irritation - 24h

Respiratory or skin sensitization:

No data available

Germ cell mutagenicity:

No data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible, or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible, or confirmed human carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible, or confirmed human carcinogen by OSHA.

Reproductive toxicity:

Suspected human reproductive toxicant



: 13 hPa (10 mmHg) @ 22°C

: 3.42 - (Air = 1.0)

11. Toxicological Information:

Specific target organ toxicity - single exposure:

No data available

Specific target organ toxicity - repeated exposure:

No data available

Aspiration Hazard:

No data available

Additional Information:

RTECS: GX0700000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin.

Cough, Shortness of breath, Headache, Nausea

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12. Ecological Information:

All work practices must be aimed at eliminating environmental contamination.

Toxicity

Toxicity to fish: LC50 - Leuciscus idus (Golden orfe) - 44 mg/l - 96h

Toxicity to daphnia and other aquatic

Invertebrates: EC50 - Daphnia magna (Water flea) - 49 mg/l - 24h

ECO - Daphnia magna (Water flea) - 22 mg/l - 24h

Toxicity to algae: EC50 - Pseudokirchneriella subcapitata (green algae) - 20 mg/l - 96h

Biodegradability: aerobic - Exposure time 20 d

Result: 92% - readily biodegradable

Bioaccumulative

Mobility in soil:

Potential: No data available

Results of PBT and

vPvB assessment: PBT/vPvB assessment not available as chemical safety assessment not required/not

conducted

No data available

Other Adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life.

13. Disposal Considerations:

Disposal Method: Dispose of waste at an appropriate waste disposal facility according to current applicable laws and

regulations.

For Large Spills : Contain material and call local authorities for emergency assistance.

Product Disposal: Dispose of at a supervised incineration facility or an appropriate waste disposal facility according to

current applicable local, state and federal laws, regulations and product characteristics at time of

disposal.

Empty Container: Contaminated container should be labeled and disposed in accordance to local, state and federal laws and

regulations.

General Comments: Refer to section 6, accidental release measures for additional information.



14. Transport Information:

| Regulatory Information | UN No. | Proper Shipping Name | UN Class | Packing Group | Labels |
|---------------------------|--------|--|----------|------------------|--|
| US DOT | 2357 | Corrosive Liquids, BASIC, Organic, N.O.S. | 8 (3) | II | Corrosive Sticker Flammable Sticker |
| IMDG | 2357 | Corrosive Liquids, BASIC, Organic, N.O.S. | 8 (3) | II | Corrosive Sticker Flammable Sticker |
| IATA | 2357 | Corrosive Liquids, BASIC, Organic, N.O.S. | 8 (3) | II | Corrosive Sticker Flammable Sticker |

15. Regulatory Information:

U.S. Federal Regulations:

SARA 302 Components: The following components are subject to reporting levels established by SARA Title III, section 302:

Cyclohexylamine CAS No. 108-91-8

SARA 313 Components: This material does not contain any chemical components with known CAS numbers that exceed the

threshold (De Minimis) reporting levels established by SARA Title III, Section 313

SARA 311/312: Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right to know Components: Cyclohexylamine CAS No. 108-91-8

Pennsylvania Right to know Components: Cyclohexylamine CAS No. 108-91-8

New Jersey Right to know Components: Cyclohexylamine CAS No. 108-91-8

New Jersey Environmental Hazardous Substances

and/or New Jersey RTK Special Hazardous: Cyclohexylamine CAS No. 108-91-8

California Proposition 65 Components: This product does not contain any chemicals known the to State of California to cause

cancer, birth defects or any other reproductive harm.

WHMIS Canada: Class B-2: Flammable liquid with a flash point lower than 37.8°C. Class D-1B: Material causing immediate

and serious toxic effects (TOXIC). Class E: Corrosive liquid

OSHA Hazcom Standard Rating: Hazardous

US Toxic Substances Control Act: Listed on the TSCA inventory

US EPA CERCLA Hazardous Substances (40 CFR 302): Not listed

US EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):

When discarded in its purchased form, this product meets the criteria of ignitability and should be managed as a hazardous waste (EPA Hazardous Waste Number D001). (40 CFR 261.20-24) When discarded in its purchased form, this product meets the criteria of corrosivity and should be managed as a hazardous waste (EPA Hazardous Waste Number D002). (40 CFR 261.20-24).



16. Other Information:

HMIS and NFPA Rating Scale:

HMIS: Hazardous Materials Identification System

Numeric Scale for Health (Blue), Flammability (Red), and Physical Hazard (Yellow):

HMIS Rating:*

| milio manigr | |
|---------------------|---|
| HEALTH | 3 |
| FLAMMABILITY | 3 |
| PHYSICAL HAZARD | 0 |
| PERSONAL PROTECTION | С |

| RATING | HEALTH | FIRE HAZARD | PHYSICAL HAZARD |
|--------|---|--|--|
| 0 | No significant risk to health | Will not burn | Product stable under ambient temperature and condition. |
| 1 | Can cause irritation or minor reversible | Must be preheated to burn | Product can become unstable at high temperatures and pressures. |
| 2 | Can cause tempo- rary or residual injury | Ignites when moderate- ly heated | Product can become unstable and cause vio- lent chemical reaction at normal pressures and temperatures |
| 3 | Can cause serious injury | Ignition occurs at nor- mal temperature | Product capable of forming explosive mix- tures and is capable of detonation in presence |
| 4 | Can be lethal from single or repeated exposure. | Extremely flammable | Product is highly explosive and unstable. Exothermic reactions possible with decomposition, polymerization, reaction with water or self reaction |

Personal Protection Code C: Gloves + Safety Goggles + Chemical Apron

NFPA: National Fire Protection Association

Numeric Scale for Health (Blue), Fire Hazard (Red), and Reactivity (Yellow):

Special (White)

NFPA Rating:*



| RATING | HEALTH | FIRE HAZARD | REACTIVITY |
|--------|---|--|---|
| 0 | Minimal Hazard | Will not burn | Normally Stable |
| 1 | Can cause signifi- cant irritation | Must be preheated to burn | Unstable at high temperatures |
| 2 | Can cause tempo- rary incapacitation or residual injury | Ignites when moder- ately heated | Normally unstable. Can readily go under violent chemical reaction but do not detonate. |
| 3 | Can cause perma- nent injury. | Ignition occurs at nor- mal temperature | Capable of detonation, or of explosive reaction, but requires a strong ignition source. |
| 4 | Can be lethal. | Extremely flammable | May explode at normal temperatures and pressures |

Revision Date: October 25, 2018

Reason for Revision: Revised "Flash Point" in Section 5 and "Physical/Chemical Properties" in Section 9.

The information contained in this SDS was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer/supplier, they are not held responsible for loss, injury, and expense arising out of the product's use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this MSDS.

